


# Unisolierte Quetschkabelschuhe

## Ringkabelschuhe

### DIN 46234 und ähnlich

ab 10 mm<sup>2</sup> nach VG 88710

Werkstoff: E-Cu, Oberfläche galvanisch verzinkt




Nennquerschnitt mm <sup>2</sup>	Nenngröße	Art.-Nr.	Abmessungen in mm				Einheit Stück
			l	d	d <sub>1</sub>	a	
0,2 – 0,5	0,5 – 2,5	<b>701392</b>	9	2,2	5	5	100
	0,5 – 3,0	<b>701394</b>	9	3,2	5	5	100
	0,5 – 3,5	<b>701396</b>	12	4,3	7	5	100
	0,5 – 4,0	<b>701398</b>	12	4,3	7	5	100
	0,5 – 5,0	<b>701400</b>	12	5,3	8	5	100
0,5 – 1,5	1,0 – 2,5	<b>701412</b>	11	2,8	6	5	100
	1,0 – 3,0	<b>701414</b>	11	3,2	6	5	100
	1,0 – 3,5	<b>701416</b>	11	3,7	6	5	100
	1,0 – 4,0	<b>701418</b>	12	4,3	8	5	100
	1,0 – 5,0	<b>701420</b>	13	5,3	10	5	100
	1,0 – 6,0	<b>701422</b>	13	6,5	10	5	100
	1,0 – 8,0	<b>701424</b>	17	8,4	14	5	100
1,5 – 2,5	1,0 – 10,0	<b>701426</b>	17	10,5	14	5	100
	2,5 – 3,0	<b>701438</b>	11	3,2	6	5	100
	2,5 – 3,5	<b>701440</b>	11	3,7	6	5	100
	2,5 – 4,0	<b>701442</b>	12	4,3	8	5	100
	2,5 – 5,0	<b>701444</b>	14	5,3	10	5	100
	2,5 – 6,0	<b>701446</b>	16	6,5	11	5	100
	2,5 – 8,0	<b>701448</b>	17	8,4	14	5	100
2,5 – 6,0	2,5 – 10,0	<b>701450</b>	17	10,5	15	5	100
	2,5 – 12,0	<b>701452</b>	20	13,0	18	5	100
	6,0 – 4,0	<b>701466</b>	14	4,3	8	6	100
	6,0 – 5,0	<b>701468</b>	15	5,3	10	6	100
	6,0 – 6,0	<b>701470</b>	16	6,5	11	6	100
	6,0 – 8,0	<b>701472</b>	19	8,4	14	6	100
	6,0 – 10,0	<b>701474</b>	21	10,5	18	6	100
10,0	6,0 – 12,0	<b>701476</b>	21	13,0	18	6	100
	6,0 – 14,0	<b>701478</b>	23	15,0	22	6	100
	10,0 – 5,0	<b>701402</b>	16	5,3	10	8	100
	10,0 – 6,0	<b>701404</b>	17	6,5	11	8	100
	10,0 – 8,0	<b>701406</b>	20	8,4	14	8	100
	10,0 – 10,0	<b>701408</b>	21	10,5	18	8	100
	10,0 – 12,0	<b>701410</b>	23	13,0	22	8	100
16,0	16,0 – 5,0	<b>701428</b>	20	5,3	11	10	100
	16,0 – 6,0	<b>701430</b>	20	6,5	11	10	100
	16,0 – 8,0	<b>701432</b>	22	8,4	14	10	100
	16,0 – 10,0	<b>701434</b>	24	10,5	18	10	100
	16,0 – 12,0	<b>701436</b>	26	13,0	22	10	100

### Ringkabelschuhe

#### DIN 46234 und ähnlich

ab 10 mm<sup>2</sup> nach VG 88710

Werkstoff: E-Cu, Oberfläche galvanisch verzinkt



Nennquerschnitt mm <sup>2</sup>	Nenngröße	Art.-Nr.	Abmessungen in mm				Einheit Stück
			l	d	d <sub>1</sub>	a	
25,0	25,0 – 5	<b>701454</b>	25	5,3	12	11	100
	25,0 – 6	<b>701456</b>	25	6,5	12	11	100
	25,0 – 8	<b>701458</b>	25	8,4	16	11	100
	25,0 – 10	<b>701460</b>	26	10,5	18	11	100
	25,0 – 12	<b>701462</b>	31	13,0	22	11	100
35,0	25,0 – 16	<b>701464</b>	35	17,0	28	11	100
	35,0 – 6	<b>701480</b>	26	6,5	15	12	100
	35,0 – 8	<b>701482</b>	26	8,4	16	12	100
	35,0 – 10	<b>701484</b>	27	10,5	18	12	100
50,0	35,0 – 12	<b>701486</b>	31	13,0	22	12	100
	35,0 – 16	<b>701488</b>	36	17,0	28	12	100
	50,0 – 6	<b>701490</b>	34	6,5	18	16	100
	50,0 – 8	<b>701492</b>	34	8,4	18	16	100
	50,0 – 10	<b>701494</b>	34	10,5	18	16	100
70,0	50,0 – 12	<b>701496</b>	36	13,0	22	16	100
	50,0 – 16	<b>701498</b>	40	17,0	28	16	100
	70,0 – 6	<b>701500</b>	38	6,5	22	18	100
	70,0 – 8	<b>701502</b>	38	8,4	22	18	100
	70,0 – 10	<b>701504</b>	38	10,5	22	18	100
95,0	70,0 – 12	<b>701506</b>	38	13,0	22	18	100
	70,0 – 16	<b>701508</b>	42	17,0	28	18	100
	95,0 – 8	<b>701510</b>	42	8,4	24	20	100
	95,0 – 10	<b>701512</b>	42	10,5	24	20	100
	95,0 – 12	<b>701514</b>	42	13,0	24	20	100
120,0	95,0 – 16	<b>701516</b>	44	17,0	28	20	100
	120,0 – 8	<b>701518</b>	44	8,4	24	22	50
	120,0 – 10	<b>701520</b>	44	10,5	24	22	50
	120,0 – 12	<b>701522</b>	44	13,0	24	22	50
150,0	120,0 – 16	<b>701524</b>	48	17,0	28	22	50
	150,0 – 10	<b>701526</b>	50	10,5	30	24	25
	150,0 – 12	<b>701528</b>	50	13,0	30	24	25
185,0	150,0 – 16	<b>701530</b>	50	17,0	30	24	25
	185,0 – 10	<b>701532</b>	50	10,5	36	28	20
	185,0 – 12	<b>701534</b>	50	13,0	36	28	20
240,0	185,0 – 16	<b>701536</b>	50	17,0	36	28	20
	240,0 – 10	<b>701538</b>	56	10,5	38	32	15
	240,0 – 12	<b>701540</b>	56	13,0	38	32	15
	240,0 – 16	<b>701542</b>	56	17,0	38	32	15